Matala

3YR IP65 IK06 ON-SITE WARRANTY 2 YEARS

Part of the Wall Lights product category

Model	Matala
Code	AMATROLED
Application	Hospitality, Outdoor, Residential, Retail



GENERAL INFORMATION

Input	220-240V
Wattage	8
Operating Temp	-20°C - 25°C
Lumens Delivered	260lm (4000K)
lm/W	37lm/W (4000K)
CCT	3000K/4000K

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without Packaging	0.734 kg
Colour / Finish	Graphite
Diameter	195 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.99

PRODUCT FEATURES

- Surface mounting ultra-slim low level circular pathway light with downward light-spill suitable for residential and hospitality applications
- Die-cast aluminium construction with graphite paint finish
- Screwless front cover with concealed allen key access provides security
- Selectable CCT between 3000K and 4000K
- Pre-wired with 1 metre of rubber insulated cable for ease of installation

Matala

3YR IP65 IK06 ON-SITE WARRANTY 2 YEARS

Part of the Wall Lights product category

Model	Matala
Code	AMATROLED
Application	Hospitality, Outdoor, Residential, Retail



