



Matala CCT



- Surface mounting ultra-slim low level circular pathway light with downward light-spill suitable for residential and hospitality applications
- Die-cast aluminium construction with graphite paint finish
- Screwless front cover with concealed allen key access
- Selectable CCT between 3000K and 4000K
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- Non-dimmable

Features

Feature 1	Surface mounting ultra-slim low level circular pathway light with downward light-spill suitable for residential and hospitality applications
Feature 2	Die-cast aluminium construction with graphite paint finish
Feature 3	Screwless front cover with concealed allen key access
Feature 4	Selectable CCT between 3000K and 4000K
Feature 5	Pre-wired with 1 metre of rubber insulated cable for ease of installation
Feature 6	Non-dimmable



General Information

Lamp Type	LED
IP Rating	IP65
IK Rating	IK06
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Wall
Warranty (Years)	3
Material	Aluminium

Technical Information

Wattage	7W
Lumens Delivered	260lm (4000K)
Lm/W	37lm/W (4000K)
CRI	80
CCT	3000/4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C - 25°C
Lumen Depreciation	L70 50,000h
Power Factor	0.903



