Merlin

Part of the Emergency product category

Model	Merlin Emergency Downlight Non-Maintained White
Code	AMED/1/W/3NM
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	5W
Operating Temp	0°C - 40°C
Lumens Delivered	248lm (Escape Route) 274lm (Open Area)
CCT	6000-7000K
Beam Angle	110

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without Packaging	0.694 kg
Colour / Finish	White
Diameter	85 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.3
L70 @ 25°C	L70 50,000h

PRODUCT FEATURES

- Ultra-low profile recessed self-test emergency downlight
- Supplied with open area and escape route interchangeable lenses
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Self-test as standard with DALI emergency option





Merlin

7YR | Li-Pro 7YR | IP20 | IK08

Part of the Emergency product category

Model	Merlin Emergency Downlight Non-Maintained White
Code	AMED/1/W/3NM
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Retail



