



Merlin



Part of the Emergency product category

Model Merlin Emergency Downlight Non-Maintained Escape Route Black
Code AMELED/ER/3NM/ST/B
Application Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	5W
Operating Temp	0°C - 40°C
Lumens Delivered	235lm (Emergency)
CCT	6500K
Beam Angle	15/135

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without	0.695 kg
Packaging	
Colour / Finish	Black
Diameter	85 mm
Height	63 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.41
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Ultra-low profile recessed self-test emergency downlight
- Option of escape route or open area models
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Self-test as standard





Merlin



Part of the Emergency product category

Model Merlin Emergency Downlight Non-Maintained Escape Route Black
Code AMELED/ER/3NM/ST/B
Application Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

