Merlin

5YR | Ni-Cd 5YR | IP20 | IK08 | ON-SITE WARRANTY 2 YEARS

Part of the Emergency product category

Model	Merlin Emergency Downlight Non-Maintained Escape Route Black
Code	AMELED/ER/3NM/ST/B
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail



GENERAL INFORMATION

Input	220-240V
Wattage	5W
Operating Temp	0°C - 40°C
Lumens Delivered	235lm (Emergency)
CCT	6500K
Beam Angle	15/135

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without Packaging	0.695 kg
Colour / Finish	Black
Diameter	85 mm
Height	63 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.41
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Ultra-low profile recessed self-test emergency downlight
- Option of escape route or open area models
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Self-test as standard

Merlin

5YR | Ni-Cd 5YR | IP20 | IK08 | ON-SITE WARRANTY 2 YEARS

Part of the Emergency product category

Model	Merlin Emergency Downlight Non-Maintained Escape Route Black
Code	AMELED/ER/3NM/ST/B
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail



