





Bulkheads






Hospitality, Outdoor, Retail



Mercurial

Mercurial 1 IP54 2CCT Multi Wattage Silver Code: AMER1/1/S/CF/SM3






Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/** only)
- Side conduit entry covers retain sleek appearance when not in use

GENERAL INFORMATION		
Wattage	20W	
Lumens Delivered	1900lm - 2700lm (4000K)	
Lm/W	135lm/W (4000K)	
Beam Angle	120	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	5°C - 40°C	
SDCM	3	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Silver	
IP Rating	IP54	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 80,000h	
Warranty (Years)	7	
CE Mark	Yes	
Diameter	370 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

