













Mercurial

Mercurial 1 IP54 2CCT Multi Wattage Silver 1-10V Code: AMER1/1/S/DD4/DM3









- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/** only)
- Side conduit entry covers retain sleek appearance when not in use

| GENERAL INFORMATION | | |
|---------------------|-------------------------|--|
| Wattage | 20W | |
| Lumens Delivered | 1900lm - 2700lm (4000K) | |
| Lm/W | 135lm/W (4000K) | |
| Beam Angle | 120 | |
| CRI | 80 | |
| CCT | 3000/4000K | |
| Input | 220-240V | |
| Operating Temp | 5°C - 40°C | |
| SDCM | 3 | |

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------|--|
| Light Source | LED | |
| Colour / Finish | Silver | |
| IP Rating | IP54 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Ceiling, Wall | |
| Lumen Depreciation | L70 80,000h | |
| Warranty (Years) | 7 | |
| CE Mark | Yes | |
| Diameter | 370 mm | |
| | | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750