



Mercurial

Mercurial 1 IP54 2CCT Multi Wattage Silver Code: AMER1/1/S/MWS/DM3


BN BN	
1 01	

Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Outdoor, Retail	
Specification	Architectural	

Bulkheads



Category



PRODUCT FEATURES

- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
 Sic
- Clip in gear tray ensures quick installation

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/** only)
- · Side conduit entry covers retain sleek appearance when not in use

Wattage Lumens Delivered Lm/W Beam Angle	13W - 20W 1900lm - 2700lm (4000K) 135lm/W (4000K)
Lm/W	
	135lm/W (4000K)
Beam Angle	
	120
CRI	80
ССТ	3000/4000K
Input	220-240V
Operating Temp	5°C - 40°C
SDCM	3

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Silver	
IP Rating	IP54	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 80,000h	
Warranty (Years)	7	
CE Mark	Yes	
Diameter	370 mm	

