





Bulkheads

Architectural

@ansell\_lighting









Hospitality, Outdoor, Retail



## **Mercurial**

## Mercurial 1 IP54 2CCT Multi Wattage Silver OCTO Code: AMER1/1/S/OCTO






Category

**Application** 

Specification



Ancillary, Commercial, Education, Healthcare,

## PRODUCT FEATURES

- $\bullet \ \ \text{Utility LED wall/ceiling luminaire suitable for education and commercial applications and}$ ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation

www.ansell-lighting.com

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/\*\* only)
- Side conduit entry covers retain sleek appearance when not in use

| GENERAL INFORMATION              |                         |  |
|----------------------------------|-------------------------|--|
| Wattage                          | 20W                     |  |
| Lumens Delivered                 | 1900lm - 2700lm (4000K) |  |
| Lm/W                             | 135lm/W (4000K)         |  |
| Beam Angle                       | 120                     |  |
| CRI                              | 80                      |  |
| CCT                              | 3000/4000K              |  |
| Input                            | 220-240V                |  |
| Operating Temp                   | -20°C - 40°C            |  |
| SDCM                             | 3                       |  |
| Product Weight without Packaging | 1.261 kg                |  |

| TECHNICAL INFORMATION          |               |  |
|--------------------------------|---------------|--|
| Light Source                   | LED           |  |
| Colour / Finish                | Silver        |  |
| IP Rating                      | IP54          |  |
| Class Protection               | 2             |  |
| Internal / External            | Internal      |  |
| Surface / Recessed / Suspended | Ceiling, Wall |  |
| Lumen Depreciation             | L70 80,000h   |  |
| Warranty (Years)               | 7             |  |
| CE Mark                        | Yes           |  |
| Diameter                       | 370 mm        |  |