



@ansell_lighting



ansellighting





Ansell Lighting



ansell_lighting

Mercurial

Mercurial 2 IP54 2CCT Silver Switch Dim DALI-
Code: AMER2/1/S/DD1/DM3



- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- Corridor function options available for effective reduction in energy consumption
- Clip in gear tray ensures quick installation
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/** only)
- Side conduit entry covers retain sleek appearance when not in use

| GENERAL INFORMATION | |
|---------------------|-----------------------|
| Wattage | 23W/34W |
| Lumens Delivered | 3200 - 4700lm (4000K) |
| Lm/W | 140lm/W (4000K) |
| Beam Angle | 120 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220-240V |
| Operating Temp | 5°C - 40°C |
| SDCM | 3 |

| TECHNICAL INFORMATION | |
|--------------------------------|---------------|
| Light Source | LED |
| Colour / Finish | Silver |
| IP Rating | IP54 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Wall |
| Lumen Depreciation | L70 80,000h |
| Warranty (Years) | 7 |
| CE Mark | Yes |
| Diameter | 500 mm |

