


Gamma Mini

Gamma Mini CCT Emergency Code: AMGAMLED/CCT/M3








Category

Application

Specification



Ancillary, Commercial, Hospitality, Residential, Retail

- Ultra slim modern polycarbonate wall/ceiling light suitable for education, residential and ancillary applications
- CCT selectable between 3000K and 4000K
- Microwave sensor set to 15 minutes at 3 metres (non-adjustable)
- /MWS and MWS/M3 has integral photocell isolation switch

- · Matt white finish to body and diffuser with optional chrome trim ring
- · Rear fixing bracket and terminal housing for ease of installation
- /MWS and /MWS/M3 versions operate as Primary and can be used in conjunction with standard Secondary

Bulkheads

Performance

• Non-dimmable

| GENERAL INFORMATION | | |
|----------------------------------|-----------------|--|
| Wattage | 10W | |
| Lumens Delivered | 1200lm (4000K) | |
| Lm/W | 115lm/W (4000K) | |
| Beam Angle | 110 | |
| CRI | 80 | |
| ССТ | 3000/4000K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 35°C | |
| SDCM | 6 | |
| Product Weight without Packaging | 0.817 kg | |
| | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------------|--|
| Light Source | LED | |
| Colour / Finish | Matt White | |
| IP Rating | IP54 | |
| Class Protection | 2 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Wall | |
| Lumen Depreciation | L70 54,000h | |
| Warranty (Years) | 3 | |
| CE Mark | Yes | |
| Diameter | 250 mm | |
| Accessories | AGAMLEDBZ/CH | |

