

## Gamma Mini

Gamma Mini CCT Code: AMGAMLED/CCT

Category	Bulkheads
Application	Ancillary, Commercial, Hospitality, Residential, Retail
Specification	Performance



## PRODUCT FEATURES

- Ultra slim modern polycarbonate wall/ceiling light suitable for education, residential and ancillary applications
- CCT selectable between 3000K and 4000K
- Microwave sensor set to 15 minutes at 3 metres (non-adjustable)
- /MWS and MWS/M3 has integral photocell isolation switch

- - · Matt white finish to body and diffuser with optional chrome trim ring
  - · Rear fixing bracket and terminal housing for ease of installation
  - /MWS and /MWS/M3 versions operate as Primary and can be used in conjunction with standard Secondary
  - Non-dimmable

GENERAL INFORMATION			
Wattage	10W		
Lumens Delivered	1200lm (4000K)		
Lm/W	115lm/W (4000K)		
Beam Angle	110		
CRI	80		
CCT	3000/4000K		
Input	220-240V		
Operating Temp	-5°C - 35°C		
SDCM	6		
Product Weight without Packagi	ing 0.77 kg		

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Matt White		
IP Rating	IP54		
Class Protection	2		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Wall		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	3		
CE Mark	Yes		
Diameter	250 mm		
Accessories	AGAMLEDBZ/CH		