Gamma

Part of the Bulkheads product category

Model	OCTO Gamma Mini Connected by WiZ
Code	AMGAMLED/OCTOW
Application	Ancillary, Commercial, Hospitality, Residential, Retail



GENERAL INFORMATION

Input	220-240V
Wattage	10W
Operating Temp	-5°C - 35°C
Lumens Delivered	750lm - 830lm (2700K - 6500K)
lm/W	77lm/W - 86lm/W (2700K - 6500K)
CCT	2700-6500K
Beam Angle	110

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	0.802 kg
Colour / Finish	Matt White
Diameter	250 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.8
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Ultra slim modern polycarbonate wall/ceiling light suitable for education, residential and ancillary applications
- Connects directly to your WiFi network using Bluetooth technology to support seamless pairing
- Matt white finish to body and diffuser with optional chrome trim ring
- Rear fixing bracket and terminal housing for ease of installation
- Tunable between 2700K - 6500K via WiZ app and voice control

ACCESSORIES

AMGAMLEDBZ/CH	Gamma Mini Chrome Trim Ring

Gamma

Part of the Bulkheads product category

Model	OCTO Gamma Mini Connected by WiZ
Code	AMGAMLED/OCTOW
Application	Ancillary, Commercial, Hospitality, Residential, Retail



