



Lynx



Part of the Bulkheads product category

Model	Lynx Mini CCT Wallpack
Code	AMLWPLED/CCT
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	15W
Operating Temp	-10°C - 40°C
Lumens Delivered	1200lm (4000K)
lm/W	78lm/W (4000K)
CCT	3000/4000K
Beam Angle	25/75

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without	0.561 kg
Packaging	
Colour / Finish	Black
Height	271 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.9
L70 @ 25°C	L70 B50 36,000h

PRODUCT FEATURES

- Robust compact wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- All polycarbonate vandal resistant body
- Tamper-proof allen key screws supplied as standard
- Multiple conduit entry and BESA box fixing points
- Hinged front face allows for a quick and easy installation





Lynx



Part of the Bulkheads product category



Model Lynx Mini CCT Wallpack

Code AMLWPLED/CCT

Application Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

