



@ansell_lighting



ansellighting



Ansell Lighting




ansell_lighting

Nappa

Nappa CCT Multi Wattage Corridor Function Self-Code: ANAPLED/G/CF/SM3

| | |
|---------------|--|
| Category | Bulkheads |
| Application | Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail |
| Specification | Performance |



- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for education, commercial and industrial applications
- One product with integral switches for multi-wattage and selectable CCT options
- Powered by Tridonic

- Tamper-proof stainless steel allen key screws
- Non-dimmable

| GENERAL INFORMATION | |
|---------------------|--------------------------|
| Wattage | 27W |
| Lumens Delivered | 2500lm - 3500lm (4000K) |
| Lm/W | 134lm/W - 127lm/W(4000K) |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220-240V |
| Operating Temp | 0°C - 40°C |
| SDCM | 5 |

| TECHNICAL INFORMATION | |
|--------------------------------|---------------|
| Light Source | LED |
| Colour / Finish | Graphite |
| IP Rating | IP66 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Ceiling, Wall |
| Lumen Depreciation | L70 60,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 298 mm |

