# NouLine

Part of the Battens and Weatherproofs product category

| | |
|---|---|
| **Model** | NouLine Batten 1200mm CCT XPRESS Self-Test Emergency |
| **Code** | ANOU4/3/SM3 |
| **Application** | Ancillary, Commercial, Industrial |

## GENERAL INFORMATION

| | |
|---|---|
| **Input** | 220-240V |
| **Wattage** | 18W/23W/28W/32W |
| **Operating Temp** | 0°C to 40°C |
| **Lumens Delivered** | 2600lm - 5100lm (4000K) |
| **lm/W** | 155lm/W (4000K) |
| **CCT** | 3000K/4000K/6500K |
| **Beam Angle** | 110/150 |

## MATERIAL INFORMATION

| | |
|---|---|
| **Main Material** | Aluminium |
| **Diffuser Material** | Polycarbonate |
| **Product Weight without Packaging** | 1.3 kg |
| **Colour / Finish** | White |
| **Height** | 64 mm |

## TECHNICAL INFORMATION

| | |
|---|---|
| **Class Protection** | 1 |
| **Light Source** | LED |
| **SDCM (Initial Macadam)** | 5 |
| **CRI** | 80 |
| **Internal / External** | Internal |
| **Surface / Recessed / Suspended** | Ceiling, Suspended |
| **Power Factor** | 0.8 |

## PRODUCT FEATURES

- High performance LED batten suitable for industrial applications and ancillary areas
- High efficiency up to 155lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Instant light output with unlimited switching
- Push fit terminals for ease and speed of installation

## ACCESSORIES

| | |
|---|---|
| AXPL/MWS/1 | XPRESS Linear Clip-in Microwave Sensor On/Off |
| AZH/RP/1 | Sensor Remote Programmer |





# NouLine

Part of the Battens and Weatherproofs product category

| | |
|---|---|
| **Model** | NouLine Batten 1200mm CCT XPRESS Self-Test Emergency |
| **Code** | ANOU4/3/SM3 |
| **Application** | Ancillary, Commercial, Industrial |















