



NouLine



Part of the Battens and Weatherproofs product category

Model	NouLine Batten 1500mm CCT Self-Test Emergency
Code	ANOU5/2/SM3
Application	Ancillary, Commercial, Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	50W/25W
Operating Temp	0°C to 30°C
Lumens Delivered	3600lm - 6900lm (4000K)
lm/W	140lm/W
CCT	3000K/4000K/6500K
Beam Angle	110/150

MATERIAL INFORMATION


Main Material	Steel, SPCC
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.36 kg
Colour / Finish	White

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- High performance LED batten suitable for industrial applications and ancillary areas
- High efficiency up to 140lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Instant light output with unlimited switching
- Push fit terminals for ease and speed of installation





NouLine



Part of the Batten and Weatherproofs product category

Model NouLine Batten 1500mm CCT Self-Test Emergency
Code ANOU5/2/SM3
Application Ancillary, Commercial, Industrial

