NouLine

Part of the Battens and Weatherproofs product category

Model	NouLine Batten 1500mm CCT XPRESS
Code	ANOU5/3
Application	Ancillary, Commercial, Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	25W/32W/38W/45W
Operating Temp	-20°C to 40°C
Lumens Delivered	3600lm / 6900lm (4000K)
lm/W	155lm/W (4000K)
CCT	3000K/4000K/6500K
Beam Angle	110/150

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.29 kg
Colour / Finish	White
Height	64 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	5
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.8

PRODUCT FEATURES

- High performance LED batten suitable for industrial applications and ancillary areas
- High efficiency up to 155lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Instant light output with unlimited switching
- Push fit terminals for ease and speed of installation

ACCESSORIES

AXPL/1/3NM	XPRESS Linear Emergency Kit
AXPL/1/3NM/DA	XPRESS Linear DALI Emergency Kit
AXPL/MWS/1	XPRESS Linear Clip-in Microwave Sensor On/Off
AZH/RP/1	Sensor Remote Programmer





NouLine

Part of the Battens and Weatherproofs product category

Model	NouLine Batten 1500mm CCT XPRESS
Code	ANOU5/3
Application	Ancillary, Commercial, Industrial













