





NouLine

NouLine Batten 1800mm CCT Self-Test Emergency
Code: ANOU6/2/SM3

| | |
|----------------------|-----------------------------------|
| Category | Battens and Weatherproofs |
| Application | Ancillary, Commercial, Industrial |
| Specification | Performance |



- High performance LED batten suitable for industrial applications and ancillary areas
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Push fit terminals for ease and speed of installation
- Non-dimmable

- High efficiency up to 140lm/W
- Instant light output with unlimited switching
- Multiple conduit entry and BESA fixing points

| GENERAL INFORMATION | |
|----------------------------------|-------------------------|
| Wattage | 50W/35W |
| Lumens Delivered | 4900lm - 6900lm (4000K) |
| Lm/W | 140lm/W |
| Beam Angle | 110/150 |
| CRI | 80 |
| CCT | 3000K/4000K/6500K |
| Input | 220-240V |
| Operating Temp | 0°C to 30°C |
| SDCM | 3 |
| Product Weight without Packaging | 1.48 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|--------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 1 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Suspended |
| Lumen Depreciation | L70 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |

