






Anzo

Anzo MultiLED 300mm CCT Adjustable Downlight Code: ANZOLED300/CCT

| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Residential, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Ultra-slim adjustable LED performance downlight suitable for semi-commercial and residential applications
- Innovative bracket / spring design for variable cut-outs from 120-260mm
- ANZOLED/CCT Non-dimmable
- ANZOLED300/CCT/PIR adjustable PIR
- Integral switches for multiple wattages and selectable CCT
- Pre-wired with 300mm cable
- ANZOLED/CCT/DIM Triac dimmable as standard

| GENERAL INFORMATION | |
|----------------------------------|---------------------------|
| Wattage | 16W - 22W |
| Lumens Delivered | 1900lm - 2600lm (4000K) |
| Lm/W | 121lm/W - 116lm/W (4000K) |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 3000/4000/6000K |
| Input | 220/240V |
| Operating Temp | -10°C - 40°C |
| SDCM | 6 |
| UGR | 25 |
| Cut-Out Size | 120-260mm |
| Product Weight without Packaging | 0.68 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Recessed |
| Lumen Depreciation | L70 54,000h |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Diameter | 300 mm |
| Height | 20 mm |

