



Ancillary, Commercial, Residential, Retail



Downlights

Performance








Anzo

Anzo MultiLED 300mm CCT Adjustable Downlight Code: ANZOLED300/CCT







Category

Application

Specification



PRODUCT FEATURES

- Ultra-slim adjustable LED performance downlight suitable for semi-commercial and residential applications
- Innovative bracket / spring design for variable cut-outs from 120-260mm
- ANZOLED/CCT Non-dimmable
- ANZOLED300/CCT/PIR adjustable PIR

www.ansell-lighting.com

- Integral switches for multiple wattages and selectable CCT
- · Pre-wired with 300mm cable
- ANZOLED/CCT/DIM Triac dimmable as standard

GENERAL INFORMATION		
Wattage	16W - 22W	
Lumens Delivered	1900lm - 2600lm (4000K)	
Lm/W	121lm/W - 116lm/W (4000K)	
Beam Angle	110	
CRI	80	
ССТ	3000/4000/6000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	6	
UGR	25	
Cut-Out Size	120-260mm	
Product Weight without Packagi	ing 0.68 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Recessed	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	3	
CE Mark	Yes	
Diameter	300 mm	
Height	20 mm	