



Opti-Linear

Part of the High/Low Bay product category



Model	Opti-Linear Low Bay 1
Code	AOLLBLED/1
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	75W
Operating Temp	-30°C - 45°C
Lumens Delivered	11000lm
lm/W	144lm/W
CCT	4000K
Beam Angle	50/100

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without	1.78 kg
Packaging	
Colour / Finish	White
Height	49 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	5
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- LED low bay suitable for industrial and commercial applications
- Ideal for any retro-fit applications replacing any traditional light sources
- Fast install/wiring via access hatch on the back of the product with push fit terminals
- Instant light output and unlimited switching
- Supplied c/w 1.5 metre catenary suspension kit





Opti-Linear

Part of the High/Low Bay product category



Model Opti-Linear Low Bay 1
Code AOLLBLED/1
Application Industrial

