





Streetlights

Performance








Onix

Onix Street Light 1

Code: AONIXLED/1







Category

Application

Specification



Commercial, Education, Healthcare, Outdoor

PRODUCT FEATURES

- Modern die-cast aluminium street light suitable for residential and commercial applications
- UV stabilized polycarbonate cover
- Built in anti-tamper isolation facility
- G3 Glare Rating

- Die-cast aluminium construction for optimal heat dissipation and performance
- Toolless gear tray removal for ease of maintenance
- Compatible with post top or side entry utility 76mm spigot
- Surge protection

GENERAL INFORMATION		
Wattage	14W	
Lumens Delivered	2000lm	
Lm/W	150lm/W	
Beam Angle	120/70	
CRI	70	
CCT	5000K	
Input	220-240V	
Operating Temp	-20°C - 50°C	
SDCM	5	
Product Weight without Packaging	3.76 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Graphite	
IP Rating	IP66	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Pole, Wall	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	237 mm	
Accessories	AONIXLED/SBA, AONIXLED/WB	