



Osprey

Part of the Emergency product category



Model	Osprey High Rack Bulkhead Cold Store Maintained / Non-Maintained
Code	AOSLED/3M/CS
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	9.5W
Operating Temp	-30°C - 5°C
Lumens Delivered	354lm (Emergency), 445lm (Standard)
CCT	6500K
Beam Angle	60/100

MATERIAL INFORMATION

Product Weight without	1.2 kg
Packaging	
Colour / Finish	White
Height	69 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall

PRODUCT FEATURES

- Modern slim profile IP65 LED polycarbonate bulkhead
- Compact high polished reflector design to provide required light level from high mounting heights
- High performance LEDs and optical performance allows increased spacing ratios
- Cold store option incorporates an intelligent integral heat management system to operate in cold store applications down to -30°C
- Selectable self-test/manual test as standard.





Osprey

Part of the Emergency product category



Model Osprey High Rack Bulkhead Cold Store Maintained / Non-Maintained
Code AOSLED/3M/CS
Application Industrial

