



Osprey

Part of the Emergency product category



Model	Osprey High Rack Bulkhead Lithium Maintained / Non-Maintained
Code	AOSLED/3M/ST
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	8W
Operating Temp	0°C - 40°C
Lumens Delivered	405lm (Emergency), 550lm (Standard)
CCT	6500K
Beam Angle	60/100

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.89 kg
Colour / Finish	White
Height	69 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.5
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Modern slim profile IP65 LED polycarbonate bulkhead
- Compact high polished reflector design to provide required light level from high mounting heights
- High performance LEDs and optical performance allows increased spacing ratios
- Selectable self-test/manual test as standard.
- Aesthetically designed for modern appearance





Osprey

Part of the Emergency product category



Model	Osprey High Rack Bulkhead Lithium Maintained / Non-Maintained
Code	AOSLED/3M/ST
Application	Industrial

