



@ansell\_lighting



ansellighting




Ansell Lighting



ansell\_lighting

## Otto LED CCT Suspended Linear - Digital

**Code:** AOTLED5/CCT/DD1/MWS/M3



- Architectural suspended linear for office, retail and educational applications
- Slim profile available in White (RAL9010) and Aluminium (RAL9006)
- Supplied bi-directional light output as standard (directional only option can be selected if required)
- Supplied c/w 1.5m suspension kit as standard

- Die-Cast aluminum end caps
- Selectable CCT between 3000K and 4000K output
- Suitable for individual or continuous suspension
- Outperforms 28W and T5 fluorescent equivalent

| GENERAL INFORMATION |                                |
|---------------------|--------------------------------|
| Wattage             | 45W                            |
| Lumens Delivered    | 4052lm (4000K), 3861lm (3000K) |
| Lm/W                | 92lm/W (4000K), 86lm/W (3000K) |
| CRI                 | Ra 80                          |
| CCT                 | 3000/4000K                     |
| Input               | 230V                           |
| Operating Temp      | -25 to 50°C                    |
| SDCM                | 3                              |

| TECHNICAL INFORMATION          |            |
|--------------------------------|------------|
| Light Source                   | LED        |
| IP Rating                      | IP20       |
| Class Protection               | 1          |
| Internal / External            | Internal   |
| Surface / Recessed / Suspended | Suspended  |
| Warranty (Years)               | 5          |
| CE Mark                        | Yes        |
| Accessories                    | AOTLED/90B |

