














## **Oxford**

## Oxford CCT Surface Linear Multi Wattage Code: AOXL4/1/MWS/SM3









- Surface linear suitable for educational and commercial applications
- This is a widely used style of fitting within the educational sector
- Steel body with polycarbonate diffuser and plastic end caps
- Powered by Philips

- Modern fully enclosed surface luminaire with curved low profile appearance
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- · Dimmable options

GENERAL INFORMATION	
Wattage	21W - 32W
Lumens Delivered	2900lm - 5000lm (4000K)
Lm/W	140lm/W
Beam Angle	110
CRI	80
CCT	3000/4000/5000K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
UGR	24
Energy efficiency class	C
Product Weight without Packaging	2.1 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling	
Lumen Depreciation	L70 80,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	70 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750