



Category	Commercial Linear
Application	Commercial, Education, Healthcare
Specification	Performance

Oxford

Oxford CCT Surface Linear Multi Wattage 1500mm Microwave Sensor Self-Test Emergency Code: AOXL5/1/MWS/SM3



PRODUCT FEATURES

- Surface linear suitable for educational and commercial applications
- This is a widely used style of fitting within the educational sector
- Steel body with polycarbonate diffuser and plastic end caps
- Powered by Philips

•	Modern fully e	enclosed surface	luminaire with	curved low profile	appearance
---	----------------	------------------	----------------	--------------------	------------

- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Dimmable options

GENER	RAL INFORMATION
Wattage	22W - 38W
Lumens Delivered	3100lm - 5400lm (4000K)
Lm/W	140lm/W
Beam Angle	110
CRI	80
ССТ	3000/4000/5000K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
UGR	24
Energy efficiency class	С
Product Weight without Packaging	2.4 kg

TECHNICA	L INFORMATION
Light Source	LED
Colour / Finish	White
IP Rating	IP20
IK Rating	IK06
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling
Lumen Depreciation	L70 80,000h
Warranty (Years)	5
CE Mark	Yes
Height	70 mm
Emergency Output Duration	3 Hr

ansell_lightingAnsell Lighting







Category	Commercial Linear	
Application	Commercial, Education, Healthcare	
Specification	Performance	

Oxford

Oxford CCT Surface Linear Multi Wattage 1500mm Microwave Sensor Self-Test Emergency Code: AOXL5/1/MWS/SM3









