









Commercial Linear

Performance


Commercial, Education, Healthcare



## **Oxford**

## Oxford CCT Surface Linear Multi Wattage Code: AOXL6/1/DD4






Category

**Application** 

Specification



- Surface linear suitable for educational and commercial applications
- This is a widely used style of fitting within the educational sector
- Steel body with polycarbonate diffuser and plastic end caps
- Powered by Philips

- Modern fully enclosed surface luminaire with curved low profile appearance
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- · Dimmable options

GENERAL INFORMATION		
Wattage	49W	
Lumens Delivered	4500lm - 6900lm (4000K)	
Lm/W	140lm/W	
Beam Angle	110	
CRI	80	
CCT	3000/4000/5000K	
Input	220-240V	
Operating Temp	-20°C - 40°C	
SDCM	3	
UGR	24	
Energy efficiency class	C	
Product Weight without Packaging	3.19 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling	
Lumen Depreciation	L70 80,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	70 mm	



