



Oxford



Part of the Commercial Linear product category

Model Oxford CCT Surface Linear Multi Wattage 1800mm
Code AOXL6/1
Application Commercial, Education, Healthcare

GENERAL INFORMATION

Input	220-240V
Wattage	32W - 49W
Operating Temp	-20°C - 40°C
Lumens Delivered	4500lm - 6900lm (4000K)
lm/W	140lm/W
CCT	3000/4000/5000K
UGR	24
Beam Angle	110

MATERIAL INFORMATION

Main Material	Steel
Diffuser Material	Polycarbonate
Product Weight without Packaging	2.56 kg
Colour / Finish	White
Height	70 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Surface linear suitable for educational and commercial applications
- Modern fully enclosed surface luminaire with curved low profile appearance
- This is a widely used style of fitting within the educational sector
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Steel body with polycarbonate diffuser and plastic end caps





Oxford



Part of the Commercial Linear product category

Model Oxford CCT Surface Linear Multi Wattage 1800mm
Code AOXL6/1
Application Commercial, Education, Healthcare

