




Pace UGR<19 600x600

Pace Backlit 600x600 Panel UGR<19 Cool White
Code: APAC1/60/1/CW/DD1

| | |
|---------------|--|
| Category | Commercial Panels |
| Application | Ancillary, Commercial, Education, Healthcare, Industrial, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Backlit LED panel suitable for education, commercial and ancillary area applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Dimmable and OCTO options available
- Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC
- Slimline design allows for installation into shallow ceiling voids
- Cool white, warm white and daylight options
- TPa as standard
- Self-Test Panel Pod and Sensor Pod compatible

| GENERAL INFORMATION | |
|----------------------------------|--------------|
| Wattage | 28W |
| Lumens Delivered | 3400lm |
| Lm/W | 120lm/W |
| Beam Angle | 90 |
| CRI | 80 |
| CCT | 4000K |
| Input | 220/240V |
| Operating Temp | -20°C - 40°C |
| SDCM | 3 |
| UGR | 18 |
| Cut-Out Size | 585x585mm |
| Product Weight without Packaging | 1.65 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|------------------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP40 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Recessed, Suspended |
| Lumen Depreciation | L80 60,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 32 mm |

