

@ansell_lighting



ansellighting



Ansell Lighting





ansell_lighting

Pace CCT MultiWattage 600x600 UGR<19

Pace Backlit CCT Multi Wattage 600x600 Panel

Code: APAC1/60/1/OCTO

| | |
|---------------|------------------------------------------------------------------|
| Category | Commercial Panels |
| Application | Ancillary, Commercial, Education, Healthcare, Industrial, Retail |
| Specification | Performance |



- Backlit LED panel suitable for education, commercial and ancillary area applications
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Dimmable and OCTO options available
- Switch Dim, DALI and 1-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC
- Slimline design allows for installation into shallow ceiling voids
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- TPa as standard
- Compatible with either the self-test panel pod or the sensor pod

| GENERAL INFORMATION | |
|----------------------------------|------------------------|
| Wattage | 30W |
| Lumens Delivered | 2500lm - 3700lm(4000K) |
| Lm/W | 125lm/W (4000K) |
| Beam Angle | 90 |
| CRI | 80 |
| CCT | 3000K-4000K-6500K |
| Input | 220-240V |
| Operating Temp | -20°C - 40°C |
| SDCM | 3 |
| UGR | 19 |
| Cut-Out Size | 585x585mm |
| Energy efficiency class | E |
| Product Weight without Packaging | 2.023 kg |

| TECHNICAL INFORMATION | |
|-----------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Lumen Depreciation | L80 60,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |

