




# Pace 1200x600

Pace Backlit 1200x600 Panel Daylight Switch Dim  
Code: APACLED1/120/DL/DD1/DM3

|               |  |
|---------------|--|
| Category      | Commercial Panels  |
| Application   | Ancillary, Commercial, Education, Healthcare, Industrial, Retail |
| Specification | Performance  |



## PRODUCT FEATURES

- Backlit LED panel suitable for education, commercial and ancillary area applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Self-Test Panel Pod and Sensor Pod compatible
- TPa as standard
- Slimline design allows for installation into shallow ceiling voids
- Cool white, warm white and daylight options
- Dimmable and OCTO options available
- Powered by Tridonic

| GENERAL INFORMATION |            |
|---------------------|------------|
| Wattage             | 46W        |
| Lumens Delivered    | 5500lm     |
| Lm/W                | 120lm/W    |
| Beam Angle          | 80         |
| CRI                 | 80         |
| CCT                 | 6500K      |
| Input               | 220/240V   |
| Operating Temp      | 0°C - 40°C |
| SDCM                | 3          |
| UGR                 | 17         |
| Cut-Out Size        | 585x1185mm |

| TECHNICAL INFORMATION          |                   |
|--------------------------------|-------------------|
| Light Source                   | LED               |
| Colour / Finish                | White             |
| IP Rating                      | IP44              |
| Class Protection               | 2                 |
| Internal / External            | Internal          |
| Surface / Recessed / Suspended | Ceiling, Recessed |
| Lumen Depreciation             | L80 54,000h       |
| Warranty (Years)               | 5                 |
| CE Mark                        | Yes               |
| Height                         | 35 mm             |

