



@ansell_lighting



ansellighting



Ansell Lighting




ansell_lighting

Pace 1200x300

Pace Backlit 1200x300 Panel Cool White DALI
Code: APACLED1/30/CW/DD3/DM3

| | |
|---------------|--|
| Category | Commercial Panels |
| Application | Ancillary, Commercial, Education, Healthcare, Industrial, Retail |
| Specification | Performance |



- Backlit LED panel suitable for education, commercial and ancillary area applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Self-Test Panel Pod and Sensor Pod compatible
- TPA as standard

- Slimline design allows for installation into shallow ceiling voids
- Cool white, warm white and daylight options
- Dimmable and OCTO options available
- Powered by Tridonic

| GENERAL INFORMATION | |
|---------------------|------------|
| Wattage | 27W |
| Lumens Delivered | 3400lm |
| Lm/W | 125lm/W |
| Beam Angle | 80 |
| CRI | 80 |
| CCT | 4000K |
| Input | 220-240V |
| Operating Temp | 0°C - 40°C |
| SDCM | 3 |
| UGR | 19 |
| Cut-Out Size | 285x1185mm |

| TECHNICAL INFORMATION | |
|--------------------------------|------------------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Recessed, Suspended |
| Lumen Depreciation | L80 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 34 mm |

