




Panther

Panther CCT Wallpack OCTO Smart Control
Code: APANLED/OCTO

| | |
|---------------|---------------------|
| Category | Bulkheads |
| Application | Industrial, Outdoor |
| Specification | Performance |



PRODUCT FEATURES

- Durable compact wall mounted luminaire for general accent illumination and suitable for industrial applications
- Multiple conduit entry and BESA box fixing points
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- All polycarbonate construction ideal for coastal and adverse weather applications
- Selectable CCT between 3000K, 4000K and 6500K output
- Photocell and sensor options

| GENERAL INFORMATION | |
|---------------------|-----------------|
| Wattage | 25W |
| Lumens Delivered | 2300lm (4000K) |
| Lm/W | 91lm/W (4000K) |
| Beam Angle | 80 |
| CRI | 80 |
| CCT | 3000/4000/6500K |
| Input | 220-240V |
| Operating Temp | -10°C - 40°C |
| SDCM | 6 |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | Black |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Wall |
| Lumen Depreciation | L80 60,000h |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Height | 305 mm |

