Parona

Part of the Wall Lights product category

Model	Parona
Code	APCLEDWL
Application	Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	3
Operating Temp	-20°C - 25°C
Lumens Delivered	70lm
lm/W	23lm/W
CCT	3000K/4000K
Beam Angle	70

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without Packaging	0.646 kg
Colour / Finish	Graphite

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Recessed
Power Factor	0.45

PRODUCT FEATURES

- Compact low level circular LED pathway light with downward light spill suitable for residential and hospitality applications
- Die-cast aluminium construction with graphite paint finish
- CCT selectable between 3000K and 4000K
- Supplied c/w plastic installation box and pre-wired with 1 metre of rubber insulated cable for ease of installation
- Non-dimmable





Parona

3YR IP65 ON-SITE WARRANTY 2 YEARS

Part of the Wall Lights product category

Model	Parona
Code	APCLEDWL
Application	Hospitality, Outdoor, Residential, Retail









