



Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

Parona

Parona

Code: APCLEDWL

PRODUCT FEATURES

- Compact low level circular LED pathway light with downward light spill suitable for residential and hospitality applications
- CCT selectable between 3000K and 4000K
- Non-dimmable
- Die-cast aluminium construction with graphite paint finish
- Supplied c/w plastic installation box and pre-wired with 1 metre of rubber insulated cable for ease of installation

GENERAL INFORMATION

Wattage	3
Lumens Delivered	70lm
Lm/W	23lm/W
Beam Angle	70
CRI	80
CCT	3000K/4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
Cut-Out Size	90mm
Energy efficiency class	E
Product Weight without Packaging	0.646 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Graphite
IP Rating	IP65
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	3
CE Mark	Yes



Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

Parona

Parona

Code: APCLEDWL

