



Pi



Part of the Wall Lights product category

Model	Pi LED Low Level CCT Graphite
Code	APILLED/GR
Application	Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2.5
Operating Temp	-20°C - 25°C
Lumens Delivered	60lm (4000K)
lm/W	25lm/W (4000K)
CCT	3000K/4000K
Beam Angle	20/60

MATERIAL INFORMATION


Main Material	Aluminium
Product Weight without	0.218 kg
Packaging	
Colour / Finish	Graphite
Diameter	100 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.5

PRODUCT FEATURES

- Modern surface mounted ultra-slim low level light with downward light spill suitable for residential and hospitality applications
- Die-cast aluminium construction with choice of white or graphite paint finish
- Push fit loop-in loop-out terminals for ease of installation
- Anti-glare opal polycarbonate front diffuser
- CCT selectable between 3000K and 4000K





Pi



Part of the Wall Lights product category

Model	Pi LED Low Level CCT Graphite
Code	APILLED/GR
Application	Hospitality, Outdoor, Residential, Retail

