



Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

Pi Low Level

Pi LED Low Level CCT White

Code: APILLED/W

PRODUCT FEATURES

- Modern surface mounted ultra-slim low level light with downward light spill suitable for residential and hospitality applications
- Push fit loop-in loop-out terminals for ease of installation
- CCT selectable between 3000K and 4000K
- Non-dimmable
- Die-cast aluminium construction with choice of white or graphite paint finish
- Anti-glare opal polycarbonate front diffuser
- Screwless front cover with concealed allen key access provides security and a sleek design

GENERAL INFORMATION

Wattage	2.5
Lumens Delivered	60lm (4000K)
Lm/W	25lm/W (4000K)
Beam Angle	20/60
CRI	80
CCT	3000K/4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
Energy efficiency class	F
Product Weight without Packaging	0.218 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP65
IK Rating	IK06
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Wall
Warranty (Years)	3
CE Mark	Yes
Diameter	100 mm





Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

Pi Low Level

Pi LED Low Level CCT White

Code: APILLED/W

