Pi

3YR IP65 IK06 ON-SITE WARRANTY 2 YEARS

Part of the Downlights product category

Model	Pi LED Wall/Ceiling CCT White
Code	APIWCLED/W
Application	Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2.5W
Operating Temp	-20°C - 25°C
Lumens Delivered	150lm (4000K)
lm/W	63lm/W (4000K)
CCT	3000K/4000K
Beam Angle	115

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without Packaging	0.23 kg
Colour / Finish	White
Diameter	100 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.5

PRODUCT FEATURES

- Modern surface mounted ultra-slim wall/ceiling light suitable for residential and hospitality applications
- Die-cast aluminium construction with choice of white or graphite paint finish
- Push fit loop-in loop-out terminals for ease of installation
- Anti-glare toughened tempered opal glass front diffuser
- CCT selectable between 3000K and 4000K





Pi

3YR IP65 IK06 ON-SITE WARRANTY 2 YEARS

Part of the Downlights product category

Model	Pi LED Wall/Ceiling CCT White
Code	APIWCLED/W
Application	Hospitality, Outdoor, Residential, Retail









