



Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

Protector

Protector Maintained / Non-Maintained Bulkhead

Code: APLED/3M

- 20mm side, end and rear cable entries
- Hinged screwless gear tray for ease of installation

- 20mm side, end and rear cable entries
- Viewing distance 18 metres

GENERAL INFORMATION	
Wattage	3W
Lumens Delivered	167lm (Emergency), 173lm (Standard)
Beam Angle	130
CRI	70
CCT	6500K
Input	220-240V
Operating Temp	0°C - 40°C
Product Weight without Packaging	0.624 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Recessed, Wall
Lumen Depreciation	L70 50,000h
Warranty (Years)	3
CE Mark	Yes
Height	64 mm
Emergency Output Duration	3 Hr



Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

Protector

Protector Maintained / Non-Maintained Bulkhead
Code: APLED/3M

