



<b>Category</b>	Emergency
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
<b>Specification</b>	Performance

# Protector

Protector Maintained / Non-Maintained Bulkhead

**Code:** APLED/3M

- 20mm side, end and rear cable entries
- Viewing distance 18 metres
- Hinged screwless gear tray for ease of installation

GENERAL INFORMATION	
<b>Wattage</b>	3W
<b>Lumens Delivered</b>	167lm (Emergency)
<b>Beam Angle</b>	130
<b>CRI</b>	70
<b>CCT</b>	6500K
<b>Input</b>	220-240V
<b>Operating Temp</b>	0°C - 40°C
<b>Product Weight without Packaging</b>	0.624 kg

TECHNICAL INFORMATION	
<b>Light Source</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK08
<b>Class Protection</b>	1
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Recessed, Wall
<b>Lumen Depreciation</b>	L70 50,000h
<b>Warranty (Years)</b>	3
<b>CE Mark</b>	Yes
<b>Height</b>	64 mm
<b>Emergency Output Duration</b>	3 Hr



<b>Category</b>	Emergency
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
<b>Specification</b>	Performance

# Protector

Protector Maintained / Non-Maintained Bulkhead

**Code:** APLED/3M

