Guardian

3YR | Ni-Cd 2YR | IP65 | IK08 | ON-SITE WARRANTY 2 YEARS

Part of the Emergency product category

Model	Protector Maintained / Non-Maintained Bulkhead
Code	APLED/3M
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail



GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C - 40°C
Lumens Delivered	167lm (Emergency)
CCT	6500K
Beam Angle	130

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.624 kg
Colour / Finish	White
Height	64 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Recessed, Wall
Power Factor	0.33
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- 20mm side, end and rear cable entries
- Hinged screwless gear tray for ease of installation
- Viewing distance 18 metres

Guardian

3YR | Ni-Cd 2YR | IP65 | IK08 | ON-SITE WARRANTY 2 YEARS

Part of the Emergency product category

Model	Protector Maintained / Non-Maintained Bulkhead
Code	APLED/3M
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail



