



Panel Pod

Part of the Emergency product category



Model	Panel Pod PRO DALI
Code	APOD/1/3NM/DA
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C to 40°C
Lumens Delivered	190lm
CCT	6000-7000K
Beam Angle	120

MATERIAL INFORMATION

Product Weight without	0.294 kg
Packaging	
Colour / Finish	White
Height	30 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
CRI	70
Internal / External	Internal

PRODUCT FEATURES

- Integral self-test/manual test emergency pod DALI to convert any Pace and Endurance. panel to emergency, instantly.
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Simple, quick twist and lock fixing
- 6 way fast wire plug in connector for speed and ease of installation (APOD/1/3NM/DA only)
- Supplied with a pre-wired 1 Metre cable for ease of installation





Panel Pod



Part of the Emergency product category

Model	Panel Pod PRO DALI
Code	APOD/1/3NM/DA
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

