









Hospitality, Retail

Performance




Ancillary, Commercial, Education, Healthcare,

Panel Pod PRO

Panel Pod PRO DALI Emergency Code: APOD/1/3NM/DA








Application

Specification



- Integral Self-Test emergency pod DALI to convert any Pace and Endurance. panel to emergency, instantly.
- Simple, quick twist and lock fixing
- Supplied with a pre-wired 1 Metre cable for ease of installation
- Patent Protected. GB 2522285B (United Kingdom)

- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- 6 way fast wire plug in connector for speed and ease of installation (APOD/1/3NM/DA only)
- Tri-colour LED shows green for healthy running condition, red/flashing for fault conditions and white for emergency operation
- Patent Protected. EP 2957826B (Europe)

General Information	
Wattage	3W
Lumens Delivered	190lm
Beam Angle	120
CRI	70
ССТ	6000-7000K
Input	220-240V
Operating Temp	0°C to 40°C
SDCM	6
Product Weight without Packaging	0.294 kg
Input Operating Temp SDCM	220-240V 0°C to 40°C 6

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Warranty (Years)	5
CE Mark	Yes
Height	30 mm

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

