












Proline Evo

Proline EVO 1200mm CCT Microwave Sensor Code: APRE4/1/MWS

Application Commercial, Education	
- FF	
Specification Performance	





- Surface linear suitable for educational and commercial applications
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Corridor Function for dimmable microwave sensor options

- Modern contemporary fully enclosed high performance surface luminaire
- Low glare and uniform light distribution
- · Self-test emergency option
- Powered by Philips and Tridonic drivers

GENERAL INFORMATION		
Wattage	21W - 36W	
Lumens Delivered	2800lm - 4700lm (4000K)	
Lm/W	130lm/W	
Beam Angle	120	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	3	
UGR	22	
Product Weight without Packaging	3.43 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	73 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

