



Proline Evo

Part of the Commercial Linear product category



Model Proline EVO 1200mm CCT
Code APRE4/1
Application Commercial, Education

GENERAL INFORMATION

Input	220-240V
Wattage	21W - 36W
Operating Temp	-10°C - 40°C
Lumens Delivered	2800lm - 4700lm (4000K)
lm/W	130lm/W
CCT	3000/4000K
UGR	22
Beam Angle	120

MATERIAL INFORMATION

Main Material	Steel
Diffuser Material	Polycarbonate
Product Weight without Packaging	3.33 kg
Colour / Finish	White
Height	73 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Surface linear suitable for educational and commercial applications
- Modern contemporary fully enclosed high performance surface luminaire
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- Low glare and uniform light distribution
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire





Proline Evo



Part of the Commercial Linear product category

Model	Proline EVO 1200mm CCT
Code	APRE4/1
Application	Commercial, Education

