




Proline Evo

Proline EVO 1800mm CCT Switch Dim
Code: APRE6/1/DD1

| | |
|---------------|-----------------------|
| Category | Commercial Linear |
| Application | Commercial, Education |
| Specification | Performance |



PRODUCT FEATURES

- Surface linear suitable for educational and commercial applications
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Corridor Function for dimmable microwave sensor options
- Modern contemporary fully enclosed high performance surface luminaire
- Low glare and uniform light distribution
- Self-test emergency option
- Powered by Philips and Tridonic drivers

| GENERAL INFORMATION | |
|----------------------------------|-------------------------|
| Wattage | 30W - 53W |
| Lumens Delivered | 4300lm - 7400lm (4000K) |
| Lm/W | 130lm/W |
| Beam Angle | 120 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220-240V |
| Operating Temp | -10°C - 40°C |
| SDCM | 6 |
| UGR | 25 |
| Product Weight without Packaging | 4.7 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|--------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 1 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Suspended |
| Lumen Depreciation | L70 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 73 mm |

