












Proline Evo

Proline EVO 1800mm CCT Microwave Sensor Code: APRE6/1/MWS

Category	Commercial Linear Commercial, Education	
Application		
Specification	Performance	





- Surface linear suitable for educational and commercial applications
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Corridor Function for dimmable microwave sensor options

- Modern contemporary fully enclosed high performance surface luminaire
- Low glare and uniform light distribution
- · Self-test emergency option
- Powered by Philips and Tridonic drivers

GENERAL INFORMATION				
Wattage	30W - 53W			
Lumens Delivered	4300lm - 7400lm (4000K)			
Lm/W	130lm/W			
Beam Angle	120			
CRI	80			
CCT	3000/4000K			
Input	220-240V			
Operating Temp	-10°C - 40°C			
SDCM	3			
UGR	25			
Product Weight without Packaging	4.8 kg			

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP20		
Class Protection	1		
Internal / External	Internal		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	5		
CE Mark	Yes		
Height	73 mm		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

