



# Proline Evo



Part of the Commercial Linear product category

<b>Model</b>	Proline EVO 1800mm CCT
<b>Code</b>	APRE6/1
<b>Application</b>	Commercial, Education

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	30W - 53W
<b>Operating Temp</b>	-10°C - 40°C
<b>Lumens Delivered</b>	4300lm - 7400lm (4000K)
<b>lm/W</b>	130lm/W
<b>CCT</b>	3000/4000K
<b>UGR</b>	25
<b>Beam Angle</b>	120

## MATERIAL INFORMATION

<b>Main Material</b>	Steel
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	4.7 kg
<b>Colour / Finish</b>	White
<b>Height</b>	73 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Ceiling, Suspended
<b>Power Factor</b>	0.95
<b>L70 @ 25°C</b>	L70 B50 54,000h

## PRODUCT FEATURES

- Surface linear suitable for educational and commercial applications
- Modern contemporary fully enclosed high performance surface luminaire
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- Low glare and uniform light distribution
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire





# Proline Evo



Part of the Commercial Linear product category

<b>Model</b>	Proline EVO 1800mm CCT
<b>Code</b>	APRE6/1
<b>Application</b>	Commercial, Education

